



## AMIGO/RODEO

# ISUZU

### ARB DELUXE BULL BARS & WINCH BARS

<u>Year</u>	<u>Type</u>	<u>Features</u>	<u>Winches</u>	<u>Part No.</u>
1998-02	Combo Bar	Airbag Approved, Urethane Buffers, Tow Points, Black	XD9000, M8000, M6000	3448200
1990-92	Winch Bar	Recessed Indicators, Tow Points, Black	XD9000, M8000, M6000	3448040

### IPF LIGHTS & LIGHTING ACCESSORIES

<u>Year</u>	<u>Type</u>	<u>Recommended Lighting</u>
1998-02	Combo Bar	800XSD, 900XS, 900HID, 960 S/R, 868CS, 968CS, J-01
1990-92	Winch Bar	800XSD, 900XS, 900HID, 960 S/R, 868CS, 968CS, J-01

### SAFARI SNORKELS

<u>Year</u>	<u>Recommended Snorkel</u>	<u>Part No.</u>
1998-02	4JB1T, 2.8L, Diesel, Left Side Mount	SS150HF
1988-96	4JB1T, 2.8L, Diesel, Left Side Mount	SS100HF

Refer to [www.safari4x4.com.au](http://www.safari4x4.com.au) for details.

### OLD MAN EMU SUSPENSION PRODUCTS

<u>Model</u>	<u>Location</u>	<u>Description</u>	<u>Type</u>	<u>Lift</u>	<u>Quantity</u>	<u>Part No.</u>
1998-02	Front	Coil Spring - Stock/Light Load	N/A	N/A	N/A	N/A
			Shock		2	*N65/N26F
	Rear	Coil Spring - Medium Load (0lbs to GVW) - 4 door only	Spring	.75"	2	OME913
			Shock		2	N102
To 1996	Front	Leaf Spring Stock/Light Load	N/A	N/A	N/A	N/A
			Shock		2	*N65/N26F
	Rear	Heavy Constant (400lbs to GVW)	Spring	.75"	2	OMEROD11
			Shock		2	*N42/N89
To 1996	Installation	Leaf Spring Bushing Kit			2	OMESB80
		U Bolts			4	OMEU59A
		Anit Inversion Kit			1	FK14
		Greasable Shackle Kit			1	OMEGS3

\* Firmer Shock

### ARB AIR LOCKER LOCKING DIFFERENTIALS & ACCESSORIES

<u>Year</u>	<u>Axle</u>	<u>Description</u>	<u>Shaft</u>	<u>Spline</u>	<u>Ratio</u>	<u>Part No.</u>
1990 On	Front	Independent Suspension, IFS	28.4 (1.12")	17	ALL	RD94 <sup>1</sup>
1999 On	Rear	Dana 44	33.3 (1.31")	30	4.56 & UP	RD117 <sup>2</sup>
					4.13 & DN	RD117

<sup>1</sup> Some builds between December 1996 & May 1998 used an unidentified 3rd member carrier with a different ring gear bolt pattern. A 3rd member with the same ratio may be swapped from earlier or later models for Air Locker installation.

<sup>2</sup> Aftermarket Dana 44 ring and pinion ratio's of 4.56 & UP will required RD116 instead.



**TROOPER**

**ISUZU**

**ARB DELUXE BULL BARS & WINCH BARS**

<u>Year</u>	<u>Type</u>	<u>Features</u>	<u>Winches</u>	<u>Part No.</u>
1998-03	Winch Bar	Airbag Approved, Recessed Indicators, Urethane Buffers, Tow Points, Black	XD9000, M8000, M6000	3444070 <sup>1</sup>
	Winch Bar	Airbag Approved, Recessed Indicators, Urethane Buffers, Tow Points, Black	XD9000, M8000	3444060 <sup>2</sup>
1992-98	Winch Bar	Recessed Indicators, Tow Points, Black	XD9000, M8000, M6000	3444050

<sup>1</sup> ARB Bar #3444070 measures 70.5" wide and suits models with "overfenders".

<sup>2</sup> ARB bar #3444060 measures 68" wide and suits models with standard fender flares.

**IPF LIGHTS & LIGHTING ACCESSORIES**

<u>Year</u>	<u>Type</u>	<u>Recommended Lighting</u>
1992-03	ALL	800XSD, 900XS, 900HID, 960 S/R, 868CS, 968CS, J-01

**SAFARI SNORKELS**

<u>Year</u>	<u>Recommended Snorkel</u>	<u>Part No.</u>
1992-97	3.1L Diesel Snorkel	SS200HF
	3.2L, V6 Snorkel	SS225HF

Refer to [www.safari4x4.com.au](http://www.safari4x4.com.au) for details.

**OLD MAN EMU SUSPENSION PRODUCTS**

<u>Model</u>	<u>Location</u>	<u>Description</u>	<u>Type</u>	<u>Lift</u>	<u>Quantity</u>	<u>Part No.</u>
1992-02	Front	Stock/Light load	N/A	N/A	N/A	N/A <sup>1</sup>
			Shock		2	*N65/N26F
	Rear	Medium Load (0lbs to GVW)	Spring	1.0"	2	OME912 <sup>2</sup>
			Shock		2	*N15/N15C
	Rear	Heavy Load (220lbs to GVW)	Spring	1.0"	2	OME919
			Shock		2	*N15/N15C
	Rear	Heavy Constant (440lbs to GVW)	Spring	.75"	2	OME929
			Shock		2	N15

<sup>1</sup> Adjust front torsion bar for additional height after installing rear springs. Set ride height to 1/3 upper bump stop clearance and 2/3 lower bump stop clearance.

<sup>2</sup> Coil must be installed with progressive rate to the top.

1982-3/92	Front	Stock/Light load	N/A	N/A	N/A	303004 <sup>1</sup>
			Shock		2	*N65/N26F
	Rear	Heavy Load (440lbs to GVW)	Spring	.75"	2	CS028R <sup>3</sup>
			Shock		2	N88
	Installation	Leaf Spring Bushing Kit			2	OMESB90
	Optional	Rear Extra Leaf				RODXL <sup>2</sup>

<sup>1</sup> Adjust front torsion bar for additional height after installing rear springs. Set ride height to 1/3 upper bump stop clearance and 2/3 lower bump stop clearance.

<sup>2</sup> Extra Leaf can be fitted for heavier constant load carrying ability.

<sup>3</sup> For Light Load applications, the 3rd leaf from the top of the spring pack can be removed for improved ride comfort.

\* Firmer shock.

**ARB AIR LOCKER LOCKING DIFFERENTIALS & ACCESSORIES**

<u>Year</u>	<u>Axle</u>	<u>Description</u>	<u>Shaft</u>	<u>Spline</u>	<u>Ratio</u>	<u>Part No.</u>
1990 On	Front	Independent Suspension, IFS	28.4 (1.12")	17	ALL	RD94
1987-91	Rear	V6 Models Only	33.5 (1.32")	26	ALL	RD44
1993-97	Rear	All Models	33.5 (1.32")	26	ALL	RD44
1998-99	Rear	Non-LSD Models	38.1 (1.50")	23	ALL	RD85
2000 On	Rear	LSD Models <sup>1</sup>	38.1 (1.50")	23	ALL	NA <sup>1</sup>

<sup>1</sup> Third member may be swapped from pre-2000 non-LSD model for RD85 fitment.